



Bulky is an uncoated mechanical book paper grade for especially high volume print runs.

- Available in many options of bulk
- High runnability

PRODUCER

Anjala Mill

TYPICAL END USES

Hard and soft cover books Paperbacks Text books Children's books School books Puzzle books

PRINTING METHODS

CSWO HSWO SFO Digital

SHADE Creamy

 L* a* b* values
 L*
 a*
 b*

 ISO 5631-3 (D50/2°)
 87.6
 0.7
 7.9

TECHNICAL SPECIFICATIONS (target values)

Substance		g/m²	48	50	53	60
Bulk	ISO 534	cm³/g	2.1	2.4	2.4	2.3
Thickness	ISO 534	μm	101	120	127	140
Brightness	ISO 2470-2 (D65/10°)	%	62	62	62	62
Opacity	ISO 2471	%	93	93	94	96

REEL SPECIFICATIONS

Core: 76 mm

Trimmed width: 8500 mm Width: min. 300 mm, max. 2500 mm Diameters: min. 1000 mm, max. 1250 mm

Max. weight: 3000 kg

CERTIFICATES

EU Ecolabel FI/011/007
Quality ISO 9001
Environment ISO 14001
Healt & Safety ISO 45001
Energy ISO 50001
FSC® CoC (FSC® C015932) *

PEFC™ CoC (PEFC/02-31-86) *

(* FSC or PEFC paper is only delivered on customer request.)

For more information:

www.storaenso.com/paper-sustainability

STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C and 23°C.
- If the paper is stored in non-air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room.
- Open the protective wrapping at the moment of use.

ENVIRONMENT

Renewable fibre Recyclable paper Recyclable packaging materials