



**YUPO Europe GmbH**  
Willstätterstraße 30  
D-40549 Düsseldorf  
P+49 (0)211 520 54 30  
www.yupo.eu

**DATA SHEET:**

# FEBG 130

**Product:**

- YUPO FEBG 130 is a synthetic paper made of Polypropylene, Inorganic fillers and additives. FEBG 130 is designed for sheet Offset printing with fast ink drying time with oxidative inks, Flexo, Gravure, Letterpress, TTR and Silk Screen with solvent inks.
- This grade is designed for general graphics and is both sides printable.
- FEBG 130 ensures water resistance, chemical resistance and durability.

**Physical Properties (measured values):**

Thickness		micron	130
Basis Weight		g/m <sup>2</sup>	100.1
Density		g/cm <sup>3</sup>	0.77
Whiteness		%	98
Opacity		%	98
Gloss (Top/Bottom)		%	48
Tensile Strength	MD	kN/m	07
	CD	kN/m	20
Elongation	MD	%	130
	CD	%	30
Tear Strength	MD	mN	500
	CD	mN	290
Stiffness (Clark)	MD	s-value	60
	CD	s-value	115
Surface Resistance		Ω	1x10 <sup>11</sup>

This document is provided for informational purposes only and is not intended to be a specific agreement. YUPO Europe reserves the right to make changes to the values shown above as required to improve product performance.