



YUPO Europe GmbH

Willstätterstraße 30
D-40549 Düsseldorf
P+49 (0)211 520 54 30
www.yupo.eu

DATA SHEET:

FEBG 150

Product:

- YUPO FEBG 150 is a synthetic paper made of Polypropylene, Inorganic fillers and additives. FEBG 150 is designed for sheet Offset printing with fast ink drying time with oxidative inks, Flexo, Gravure, Letterpress, TTR and Silk Screen with solvent inks.
- This grade is designed for general graphics and is both sides printable.
- FEBG 150 ensures water resistance, chemical resistance and durability.

Physical Properties (measured values):

Thickness		micron	150
Basis Weight		g/m ²	115.5
Density		g/cm ³	0.77
Whiteness		%	98
Opacity		%	98
Gloss (Top/Bottom)		%	49
Tensile Strength	MD	kN/m	07
	CD	kN/m	20
Elongation	MD	%	135
	CD	%	25
Tear Strength	MD	mN	610
	CD	mN	350
Stiffness (Clark)	MD	s-value	75
	CD	s-value	155
Surface Resistance		Ω	1x10 ¹¹

This document is provided for informational purposes only and is not intended to be a specific agreement. YUPO Europe reserves the right to make changes to the values shown above as required to improve product performance.